



Product technical sheet

WOODEN WD1450







7 - 16 years

31 kids

45,3 m²



Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs,
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Platforms and climbing walls made of durable anti-slip and waterproof plywood or HPL plate.
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE or HPL side panels,
- Tubular sled made of stainless steel,
- Moving elements made of durable HDPE or HPL plate, resistant to weather conditions,
- Double wall tube passage made of polypropylene,
- Climbing stones made of durable HDPE plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Facilitating disability



easy access



integration



Intellectual development



thinking



Physical development



sliding



pull-up



passage crawling



climbing

M: +48 793 404 991






















Product technical sheet

WOODEN WD1450

Product data

| Length | 535 cm | |
|--------------------------------|--------------|--|
| Width | 510 cm | |
| Total height | 235 cm | |
| Age group | 7 - 16 years | |
| Number of users | 31 kids | |
| Safety zone | 45,3 m2 | |
| Free fall height | 220 cm | |
| The height of the platforms | 120, 150 cm | |
| In accordance with norm EN | 1176-1:2017 | |
| Weight of the heaviest part | 40 kg | |
| Dimensions of the largest part | 261x42x97 cm | |
| Availability of spare parts | YES | |
| Installation time | 12 h | |
| Color options | | |

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com



Surfaces according to EN 1176-1:2017

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) Particle size fro to 80 | Particle size from 20 | 30 | ≤200 |
| | to 80 | 40 | ≤300 |
| woodchips (A,C) Particle size from 5 to 30 | Particle size from 5 | 30 | ≤200 |
| | 40 | ≤300 | |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | Tested according to EN 1177 | | 220 |

Product technical sheet

WOODEN WD1450

Amount of safe surface corresponding with free fall height:

| HIC 100 | 11,8 m ² |
|---------|---------------------|
| HIC 120 | 0,5 m ² |
| HIC 150 | 4,9 m ² |
| HIC 170 | 0,6 m ² |
| HIC 190 | 3,8 m ² |
| HIC 220 | 23,7 m ² |

Data is subject to change without prior notice.

