




# Levigator 4

## Product Specification

### Description

16mm steel wire rope, low-level net for children +3 years. Challenge cognitive skills and encourage bravery by climbing on your own, or with friends. Personalise the rope net to fit the surrounding environment with rope colour: beige, black, yellow, red, green and blue.



---

## Material Specification

### Rope

#### Internal Ropes

16mm dia. FC 6-strand steel reinforced combination rope with polypropylene fibre core. Braided Nylon sheathing. Tested SWL -> 3300kg

#### Rope Connections

Aluminium/magnesium alloy one-piece seamless ferrules to DIN 1725. Tensile tested to a strength exceeding -> 145N/mm<sup>2</sup>. The ferrules are hydraulically pressed after positioning.

Cross-joint bursting strength exceeds 2500kg. Slip resistance exceeds 1000kg. Patent applies.

Hydraulically pressed one piece aluminium jaw, with security bolt.

### Steelwork

#### Central Mast – Upper/Lower

AISI 304/304 88.9mm S/S welded tube DPOL 304 with a 3mm wall; AISI 304/304 83mm S/S welded tube DPOL 304 with a 3mm wall.

#### Legs, Feet and Ties

AISI 304/304 88.9mm S/S with a 3mm Wall; stainless steel.

### Miscellaneous

#### Plastic Panel

19mm HDPE panel. (Request colour options)

#### Rubber Panel

12mm nylon reinforced rubber membrane.

---

## Product Information

**Equipment height:** 1.6m

**Safety Surface:** 7.35mOD

**Free Surface:** 8.4mOD

**Height of fall:** 1.595 m

**Number of Users:** 23 Users

**Age Group:** +3

## Freight

**Weight:** TBC

**Number Parts:** TBC

**Heaviest Part:** TBC

**Largest Part:** TBC



Type Approved  
Safety  
Regular Production  
Surveillance

www.tuv.com  
ID 2000000000

*The equipment meets the requirements of the equipment safety law and was tested according to EN1176-1(2008) by TUV Rheinland LGA Products GmbH.  
Certificate Number: R 60075344*