

WOODEN WD1452



7 - 16 years



31 kids



46,5 m²



Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Platforms made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- The covers are made of recycled HDPE panel, resistant to weather conditions
- Tubular sled made of stainless steel,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Handles made of synthetic material,
- Stainless steel bars, ladders and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Physical development



balance



sliding



pull-up



passage



climbing





4
number of towers



14
number of activity elements

Product technical sheet

WOODEN WD1452




Product data

| | |
|--------------------------------|--------------|
| Length | 528 cm |
| Width | 428 cm |
| Total height | 260 cm |
| Age group | 7 - 16 years |
| Number of users | 31 kids |
| Safety zone | 46,5 m2 |
| Free fall height | 250 cm |
| The height of the platforms | 150, 180 cm |
| In accordance with norm EN | 1176-1:2017 |
| Weight of the heaviest part | 11 kg |
| Dimensions of the largest part | 249x9x9 cm |
| Availability of spare parts | YES |
| Installation time | 9 h |
| Color options | |

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;



Guarantee

30

30 year guarantee - Structural strength of steel and stainless steel components

15

15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment

10

10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components

5

5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



Surfaces according to EN 1176-1:2017

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|------------------------------|----------------------|---------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) | Particle size from 20 to 80 | 30 | ≤200 |
| | | 40 | ≤300 |
| woodchips (A,C) | Particle size from 5 to 30 | 30 | ≤200 |
| | | 40 | ≤300 |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | Tested according to EN 1177 | | 250 |

Product technical sheet

WOODEN WD1452

Amount of safe surface corresponding with free fall height:

| | |
|---------|---------------------|
| HIC 150 | 5,3 m ² |
| HIC 180 | 2,2 m ² |
| HIC 200 | 14,2 m ² |
| HIC 250 | 26,1 m ² |

Data is subject to change without prior notice.

