

Product technical sheet

CLIMBOO 0498

ա ա ա

6 kids

19,2 m²

4+



Material specification

- Hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction of 80 x 80 mm profile,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



13/07/2023

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





biuro@vinci-play.com info@vinci-play.com www.vinci-play.com


1/3











Guarantee



30 year guarantee -Structural strength of steel and stainless steel components

Detailed information in the guarantee card

15 dynamic equipment

15 year guarantee -Structural failure of steel and stainless steel, for

10

10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Vinci Group Sp. z o.o.
Seminaryjna 9 Street
99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

Product technical sheet CLIMBOO 0498

Product data

Length	160 cm
Width	160 cm
Total height	55 cm
Age group	4+ years
Number of users	6 kids
Safety zone	19,2 m2
Free fall height	< 60 cm
In accordance with norm EN	1176-1:2017
Weight of the heaviest part	5 kg
Dimensions of the largest part	8x8x106 cm
Availability of spare parts	YES
Installation time	2 h

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited • entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of • jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep; •
- the device adapted for installation on flat terrain and • slopes; the maximum allowable slope inclination angle is 45 degrees;
- render is for reference only, the actual appearance of the equipment and its color may vary;



Surfaces according to EN 1176-1:2017


	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bork (A.C)	Particle size from 20	30	≤200
bark (A,C)	to 80	40	≤300
woodching (A_C)	Particle size from 5	30	≤200
woodchips (A,C)	to 30	40	≤300
cond or group (A.C.)	Particle size from	30	≤200
sand or gravel (A,C)	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according	to EN 1177	< 60


Product technical sheet CLIMBOO 0498

Amount of safe surface corresponding with free fall height:

|--|

Data is subject to change without prior notice.





Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com